

Family Design Series

|     |                                                                                     |                                                                                                    |                                                                                                                                                                                                                                                               |
|-----|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 312 |    | Battery Capacity: 12000mAh(44.4Wh)<br>Size: 186x98x37mm<br>Weight: 590g<br>Peak Current: 1800A     | Input: USB-C PD30W(5V/3A;9V/3A;<br>12V/2.5A;15V/2A;20V/1.5A)<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>USB-C PD30W(5V/3A; 9V/3A;<br>12V/2.5A;15V/2A;20V/1.5A)<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times             |
| 313 |    | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 244x105x32mm<br>Weight: 745g<br>Peak Current: 2500A    | Input: USB-C PD30W(5V/3A;9V/3A;<br>12V/2.5A;15V/2A;20V/1.5A)<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>USB-C PD30W(5V/3A;9V/3A;<br>12V/2.5A;15V/2A;20V/1.5A)<br>15V/10A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times   |
| 322 |    | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 245x105x41mm<br>Weight: 898g<br>Peak Current: 3250A    |                                                                                                                                                                                                                                                               |
| 333 |    | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 223x93x38mm<br>Weight: 620g<br>Peak Current: 2500A     | Input: USB-C 5V/3A<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>5V/2.4A;15V/10A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                              |
| 351 |    | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 252x98x57mm<br>Weight: 1.09kg<br>Peak Current: 3250A   | Input: USB-C PD100W(5V/3A;9V/2A;12V/3A;<br>15V/3A;20V/5A)<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>USB-C PD100W(5V/3A;9V/2A;12V/3A;<br>15V/3A;20V/5A)<br>5V/2.4A;15V/10A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |
| 536 |    | Battery Capacity: 10000mAh(37Wh)<br>Size: 175x87x36mm<br>Weight: 430g<br>Peak Current: 1500A       | Input: USB-C 5V/3A<br>Output: USB1+USB2 5V/3.4A;USB-C 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                      |
| 240 |   | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 224x89.6x36mm<br>Weight: 625g<br>Peak Current: 2500A   | Input: USB-C 15W(5V/3A)<br>Output: 5V/2.4A;Quick charge( 5V/2.4A;9V/2A;12V/1.5A)<br>USB-C 15W(5V/3A);<br>15V/10A;<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                |
| 241 |  | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 224x89.6x43.8mm<br>Weight: 775g<br>Peak Current: 3250A | Input: USB-C15W(5V/3A)<br>Output: 5V/2.4A;Quick charge( 5V/2.4A;9V/2A;12V/1.5A)<br>USB-C 15W(5V/3A);<br>15V/10A;<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                 |
| 528 |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 164x84x35mm<br>Weight: 420g<br>Peak Current: 1500A       | Input: USB-C 5V/2.4A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                                             |
| 600 |  | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 233*88*35mm<br>Weight: 750g<br>Peak Current: 3250A     | Input: USB-C 5V/2.4A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                                             |

\* All the data is from our laboratory, the design technical parameters and the suppliers. The actual data will be slightly affected by the software version, the use environment, temperature, vehicle horsepower, battery voltage and other factors. The product structure picture is a functional diagram, not an absolute actual structure, and ultimately the actual object shall prevail.

AC Series

|     |                                                                                     |                                                                                                                    |                                                                                                                                                                                                                                                                         |
|-----|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 183 |  | Battery Capacity: 18000mAh(66.6Wh)<br>Size: 224x101x34mm<br>Weight: 830g<br>Peak Current: 2750A<br>AC Output:100W  | Input: USB-C 9V/2A<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>15V/10A; 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                       |
| 316 |  | Battery Capacity: 62500mAh(225Wh)<br>Size: 238x103x98mm<br>Weight: 2.17kg<br>Peak Current: 1100A<br>AC Output:120W | Input: USB-C PD/SC100W Max(5V/3A;9V/2A;12V/3A;<br>15V/3A;20V/5A)<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>USB-C PD100W Max(5V/3A;9V/2A;12V/3A;<br>15V/3A;20V/5A); 5V/2.4A; 15V/10A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |

Waterproof Series

|     |                                                                                       |                                                                                                                    |                                                                                                                                                                                                                                                                      |
|-----|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 535 |    | Battery Capacity: 10000mAh(37Wh)<br>Size: 184x95x31mm<br>Weight: 505g<br>Peak Current: 1500A<br>IP Rating: IP65    | Input: USB-C 15W 5V/3A<br>Output: USB1+USB2 5V/3.4A; USB-C 15W 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                    |
| 533 |    | Battery Capacity: 10000mAh(37Wh)<br>Size: 188x93x35.5mm<br>Weight: 540g<br>Peak Current: 1500A<br>IP Rating: IP65  | Input: USB-C 15W 5V/3A<br>Output: USB1+USB2 5V/3.4A;USB-C 15W 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                     |
| 590 |    | Battery Capacity: 12000mAh(44.4Wh)<br>Size: 177x87x38mm<br>Weight: 550g<br>Peak Current: 1800A                     | Input: USB-C PD65W<br>Output: USB-C PD65W;<br>Quick charge(5V/3A;9V/2A;12V/1.5A)<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                        |
| 298 |    | Battery Capacity: 20000mAh(74Wh)<br>Size: 235x90x42mm<br>Weight: 992g<br>Peak Current: 3000A<br>IP Rating: IP65    | Input: USB-C PD/SC 65W (5V/3A;9V/3A;<br>12V/3A;15V/3A;20V/3.25A)<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>USB-C PD65W (5V/3A;9V/3A;12V/3A;15V/3A;<br>20V/3.25A);5V/2.4A;15V/10A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times    |
| 317 |  | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 238x105x53mm<br>Weight: 990g<br>Peak Current: 3250A<br>IP Rating: IP64 | Input: USB-C PD/SC 100W Max(5V/3A;9V/3A;<br>12V/3A;15V/3A;20V/5A)<br>Output: Quick charge (5V/3A;9V/2A;12V/1.5A)<br>USB-C PD100W Max(5V/3A;9V/3A;12V/3A;15V/3A;<br>20V/5A);15V/10A;5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |

Super Capacitor Series

|      |                                                                                       |                                                                                          |                                                                                                              |
|------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| 629  |  | Battery Capacity: 3000Fx5<br>Size: 328x113x228mm<br>Weight: 3.8kg<br>Peak Current: 1200A | Input: 5V/3A<br>Output: 12V jump starter<br>Operating Temp: -45°C~70°C<br>Cycle Life: >100,000 times         |
| 109A |  | Battery Capacity: 720Fx5<br>Size: 295x219x81mm<br>Weight: 2kg<br>Peak Current: 1200A     | Input: 5V/2A;12V/10A<br>Output: 12V jump starter<br>Operating Temp: -40°C~55°C<br>Cycle Life: >100,000 times |
| 93C  |  | Battery Capacity: 300Fx5<br>Size: 250x120x50mm<br>Weight: 1.15kg<br>Peak Current: 800A   | Input: 5V/3A;12V/5A<br>Output: 12V jump starter<br>Operating Temp: -40°C~55°C<br>Cycle Life: >100,000 times  |

10 Intelligent Protections



Over-current protection



Reverse polarity protection



Ultimate low electricity consumption protection



Over-discharge protection



Over-charge protection



Over-voltage protection



AI software protection



Short-circuit protection



Reverse-charge protection



Over-temperature protection

DSLI IV - the fourth generation smart and safe jump starter supply

European and American invention patent: EP3264515B1 / US10148105B2.  
Powered by Carku's Graphene technology enabling, it has excellent performance of AI communication recognition, the second generation intelligent temperature control, PD intelligent speed, extreme low power consumption and realizes all-round 10 intelligent security protection.The beauty of the world is in the moment when the car jump start.

Global leading supplier of jump starter

Shenzhen Carku Technology Co., Ltd was founded in 2011,which is a high-tech enterprise specializing in the research and development, production and sales of lithium battery technology application products, the drafting committee of jump starter industry standard in China.  
So far, CARKU has developed more than 600 R&D products, has obtained 852 global patents, and has passed ISO9001,IATF16949,BSCI quality management system with UL,FCC,PSE,CE,RoHS certificate.

World's First Inventor  
Quality Assurance

- National-level Manufacturing Single-Item Champion
- National Specialized and Sophisticated "Little Giant" Enterprise
- Germany IF International Design Award
- The drafting unit of the industry standards
- National Intellectual Property Advantage Enterprise

Industry Leading  
Quality Service

- National High Tech Enterprise
- China Patent Excellence Award
- SEMA Global Media Award
- MUSE Design Awards

Shenzhen Carku Technology Co.,Ltd



@CARKU



@CARKU



@carku6233



marketing@carku.com



www.car-ku.com

Add: Building A, Baoke Creative Park, Lianrun Rd, Longhua District, Shenzhen , China.

Factory Add: Carku Science & Technology Park, The China-Korea (Huizhou) Industrial Park(Phase I), Zhongkai District, Huizhou, Guangdong, China.

The drafting committee of jump starter industry standard in China  
A supplier of global professional multi-function emergency jump starter solutions

CARKU

Multi-functional Car Jump Starter Inventor



Shenzhen Carku Technology Co., Ltd

Advantage-01



DSLI-IV Patent Core Technology,  
Leading the Industry

Quicker, More Powerful and Safer

Advantage-02



Full Coverage of  
All Vehicles Types

From compact car to heavy duty truck, Instant start without worries

Advantage-03



10 Intelligent Protections,  
Safety Guarding

safety guarding in 360°

Advantage-04



Extremely low power consumption,  
No fear of battery drain

Still working, even after storage of 2 Years

12&24V Series

|      |  |                                                                                                             |                                                                                                                                                         |
|------|--|-------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| 395B |  | Battery Capacity: 36400mAh (134.7Wh)<br>Size: 252x150x188.8mm<br>Weight: 2.92kg<br>Peak Current: 2800A      | Input: USB-C (5V/2A; 9V/2A); DC 29V/5A<br>Output: 5V/2.4A; 5V/1A<br>12V&24V jump starter<br>Operating Temp: -40°C~60°C<br>Cycle Life: ≥2000 times       |
| 326B |  | Battery Capacity: 56000mAh(207.2Wh)<br>Size: 260.7x188x148.7mm<br>Weight: 2.8kg<br>Peak Current: 3500A      | Input: 29V/2A<br>Output: Quick charge(5V/3A;9V/2A;12V/1.5A)<br>12V/10A<br>12V&24V jump starter<br>Operating Temp: -40°C~60°C<br>Cycle Life: >1000 times |
| 393B |  | Battery Capacity: 136500mAh (499.59Wh)<br>Size: 295.5x175.5x245.4mm<br>Weight: 5.4kg<br>Peak Current: 7000A | Input: USB-C (5V/2A; 9V/2A); DC 29V/5A<br>Output: 5V/2.4A; 5V/1A<br>12V&24V jump starter<br>Operating Temp: -40°C~60°C<br>Cycle Life: ≥2000 times       |
| 396D |  | Battery Capacity: 176000mAh (566.72Wh)<br>Size: 340x222.5x263mm<br>Weight: 8.34kg<br>Peak Current: 4000A    | Input: USB-C (5V/2A; 9V/2A); DC 29V/5A<br>Output: 5V/2.4A; 5V/1A<br>12V&24V jump starter<br>Operating Temp: -40°C~60°C<br>Cycle Life: ≥2000 times       |

Sodium-ion Series

|      |  |                                                                                                    |                                                                                                                                                                    |
|------|--|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 625  |  | Battery Capacity: 10400mAh(31.2Wh)<br>Size: 224x89.6x43.8mm<br>Weight: 650g<br>Peak Current: 1500A | Input: USB-C 5V/3A<br>Output: USB1+USB2 5V/3.4A;USB-C 5V/3A<br>12V jump starter<br>Operating Temp: -40°C~80°C<br>Cycle Life: >1000 times                           |
| 621N |  | Battery Capacity: 13200mAh(39.6Wh)<br>Size: 220x144x46mm<br>Weight: 1.3kg<br>Peak Current: 2000A   | Input: USB-C PD30W<br>Output: Quick Charge(5V/3A;9V/2A;12V/1.5A);12V/10A;<br>USB-C PD30W;12V jump starter<br>Operating Temp: -40°C~80°C<br>Cycle Life: >1000 times |
| 627  |  | Battery Capacity: 22400mAh(67.2Wh)<br>Size: 266x239x119mm<br>Weight: 2.5kg<br>Peak Current: 3000A  | Input: 5V/2A;9V/2A<br>Output: 5V/2.1A;Quick charge (5V/3A;9V/2A);<br>12V/10A;12V jump starter<br>Operating Temp: -40°C~80°C<br>Cycle Life: >1000 times             |
| 617N |  | Battery Capacity: 38400mAh(115.2Wh)<br>Size: 277x126x156mm<br>Weight: 3kg<br>Peak Current: 2500A   | Input: PD65W<br>Output: 5V/2.4A; 12V/10A;<br>12V&24V jump starter<br>Operating Temp: -40°C~80°C<br>Cycle Life: >1000 times                                         |
| 373N |  | Battery Capacity:48000mAh(144Wh)<br>Size: 290x230x185.5mm<br>Weight: 4kg<br>Peak Current: 3200A    | Input: Quick charge(5V/2A;9V/2A); DC 31.2V/5A<br>Output: 5V/1A;5V/2.4A;<br>12V&24V jump starter<br>Operating Temp: -40°C~80°C<br>Cycle Life: >1000 times           |

Economic Series

|      |  |                                                                                                    |                                                                                                                                                 |
|------|--|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| 601  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 170x81x32mm<br>Weight: 500g<br>Peak Current: 1500A       | Input: USB-C 5V/2.4A<br>Output: USB1 5V/1A;USB2 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times               |
| 613  |  | Battery Capacity: 7500mAh(27.75Wh)<br>Size: 158x85.8x27.6mm<br>Weight: 353g<br>Peak Current: 1200A | Input: USB-C 5V/3A<br>Output: Quick charge (5V/3A;9V/2A;12V/1.5A);<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |
| 520A |  | Battery Capacity: 8000mAh(29.6Wh)<br>Size: 148x82x29.5mm<br>Weight: 320g<br>Peak Current: 1200A    | Input: USB-C 5V/2A<br>Output: 5V/2A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                   |
| 378B |  | Battery Capacity: 8000mAh(29.6Wh)<br>Size: 151x80x29mm<br>Weight: 326g<br>Peak Current: 1200A      | Input: USB-C 5V/2A<br>Output: 5V/2.1A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                 |
| 501  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 168x86x38.5mm<br>Weight: 400g<br>Peak Current: 1500A     | Input: USB-C 5V/2A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                 |
| 522  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 175x87x36mm<br>Weight: 450g<br>Peak Current: 1500A       | Input: USB-C 5V/3A<br>Output: USB1+USB2 5V/3.4A<br>USB-C 5V/3A; 12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times       |

|      |  |                                                                                                  |                                                                                                                                                                                          |
|------|--|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 530  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 175x90x34mm<br>Weight: 460g<br>Peak Current: 1500A     | Input: USB-C 5V/3A<br>Output: USB1+USB2 5V/3.4A;USB-C 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                 |
| 531  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 175x89x36mm<br>Weight: 450g<br>Peak Current: 1500A     | Input: USB-C 5V/3A<br>Output: USB1+USB2 5V/3.4A;USB-C 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                 |
| 538  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 173.3x80x36mm<br>Weight: 430g<br>Peak Current: 1500A   | Input: USB-C 5V/2.4A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                        |
| 568  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 197x90.5x34.5mm<br>Weight: 455g<br>Peak Current: 1500A | Input: USB-C 15W 5V/3A<br>Output: USB1 5V/1A; USB2 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                  |
| 580  |  | Battery Capacity: 12000mAh(44.4Wh)<br>Size: 180.5x91x37mm<br>Weight: 560g<br>Peak Current: 1800A | Input: USB-C 5V/3A<br>Output: USB-C PD45W;USB-A 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                     |
| 510  |  | Battery Capacity: 12000mAh(44.4Wh)<br>Size: 190x85.8x39mm<br>Weight: 520g<br>Peak Current: 1800A | Input: USB-C 15W 5V/3A<br>Output: USB1+USB2 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                         |
| 529  |  | Battery Capacity: 20000mAh(74Wh)<br>Size: 218x85x39mm<br>Weight: 660g<br>Peak Current: 3000A     | Input: USB-C 5V/2.4A<br>Output: 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                     |
| 386  |  | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 225x89x30mm<br>Weight: 564g<br>Peak Current: 2500A   | Input: USB-C 15W 5V/3A<br>Output: Quick charge (5V/3A;9V/2A;12V/1.5A)<br>USB-C 15W 5V/3A;5V/2.4A;15V/10A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times    |
| 387  |  | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 224x87x39mm<br>Weight: 540g<br>Peak Current: 2500A   | Input: USB-C 15W 5V/3A<br>Output: Quick charge (5V/3A;9V/2A;12V/1.5A)<br>USB-C 15W 5V/3A;5V/2.4A;15V/10A; 12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times      |
| 163D |  | Battery Capacity: 20000mAh(74Wh)<br>Size: 225x91x34mm<br>Weight: 750g<br>Peak Current: 3000A     | Input: Quick charge(5V/2A;9V/2A)<br>Output: 5V/1A;5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                   |
| 332  |  | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 220x102x41mm<br>Weight: 780g<br>Peak Current: 3250A  | Input: USB-C 15W 5V/3A<br>Output: Quick charge ( 5V/3A;9V/2A;12V/1.5A)<br>5V/2.4A; 15V/10A; USB-C 15W 5V/3A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |

Air Inflator Series

|      |  |                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                             |
|------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 605  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 124x220x52.5mm<br>Weight: 850g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI<br>Air Flow Volume: Inflate/Deflate: 150L/min                                                                                        | Input: USB-C 5V/2A<br>Output: 5V/2.1A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                          |
| 507  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 122.2x164.2x46mm<br>Weight: 670g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI<br>Battery Capacity: 10000mAh(37Wh)<br>Size: 123x166x50mm<br>Weight: 714g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI | Input: USB-C 5V/2A<br>Output: 5V/2.1A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times<br>Input: USB-C 5V/2A<br>Output: 5V/2.1A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times    |
| 557  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 200x116x54mm<br>Weight: 830g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI                                                                                                                                        | Input: USB-C 5V/2A<br>Output: 5V/2.1A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                          |
| 383  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 208x112x40mm<br>Weight: 520g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI                                                                                                                                        | Input: USB-C 5V/2A<br>Output: 5V/2.1A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                          |
| 638  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 220x127x58mm<br>Weight: 1kg<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI                                                                                                                                         | Input: USB-C 5V/2A<br>Output: 5V/2.4A<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                          |
| 615  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 197x120x56mm<br>Weight: 850g<br>Peak Current: 1500A<br>Max Inflation Pressure: 150PSI                                                                                                                                        | Input: USB-C 5V/2A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                             |
| 577  |  | Battery Capacity: 10000mAh(37Wh)<br>Size: 223x123x63mm<br>Weight: 1.5kg<br>Peak Current: 2500A<br>Max Inflation Pressure: 160PSI                                                                                                                                       | Input: USB-C 5V/2A<br>Output: 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                                             |
| 325  |  | Battery Capacity: 16000mAh(59.2Wh)<br>Size: 226x132x54mm<br>Weight: 1.48kg<br>Peak Current: 3400A<br>Max Inflation Pressure: 150PSI                                                                                                                                    | Input: USB-C 9V/2A<br>Output: 15V/10A; Quick charge (5V/3A;9V/2A;12V/1.5A)<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                     |
| 655  |  | Battery Capacity: 27000mAh(99.9Wh)<br>Size: 290.5x164.9x81mm<br>Weight: 2.25kg<br>Peak Current: 3400A<br>Max Inflation Pressure: 150PSI                                                                                                                                | Input: USB-C PD 30W<br>Output: USB-C PD 30W;5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                               |
| 632  |  | Battery Capacity: 27000mAh(99.9Wh)<br>Size: 290.5x164.9x81mm<br>Weight: 2.25kg<br>Peak Current: 3400A<br>Max Inflation Pressure: 150PSI                                                                                                                                | Input: USB-C PD 100W<br>Output: USB-C PD 100W;USB-A 5V/2.4A;12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times                                                                                                       |
| 558A |  | Battery Capacity: 24000mAh(88.8Wh)<br>Size: 230x112.5x124mm<br>Weight: 1.7kg<br>Peak Current: 3250A<br>Max Inflation Pressure: 160PSI<br>Air Flow Volume: Inflate/Deflate: 150L/min                                                                                    | Input: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A)<br>Output: USB-C PD30W (5V/3A;9V/3A;12V/2.5A;15V/2A;20V/1.5A)<br>Quick charge (5V/3A;9V/2A;12V/1.5A)<br>12V jump starter<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times |
| 612  |  | Battery Capacity: 9000mAh(33.3Wh)<br>Size: 226x74.5x40mm<br>Weight: 470g<br>Peak Current: 1500A<br>Motor Power: 200W MAX<br>Fan battery life: 92Min MAX                                                                                                                | Input: USB-C 10W (5V/2A)<br>Output: USB 5V/2.1A<br>Operating Temp: -20°C~60°C<br>Cycle Life: >1000 times<br>Gear Settings: 4 levels (Low, Medium, High, Turbo)<br>Fan Speed: 50 m/s MAX                                                     |